



**SPECIFICATION:**  
**CONTACT RESISTANCE: 30M OHM MAX**  
**30M OHM MAX**  
**INSULATOR RESISTANCE:**  
**1000M OHM MIN. AT DC 500V**  
**CURRENT RATING: 1AM**  
**DIELECTRIV WITHSTANDING VOL TAGE**  
**AC 500V FOR 1 MINUTE**  
**OPERATING TEMPERATURE:**  
**-40°C ~+105°C**  
**CONTACT MATERIAL: BRASS**  
**INSULATOR MATERIAL:**  
**P B T & 30% GLASS FIBER UL 94V-0**

PART NO	A	B	C
10	10.16	18.16	22.96
14	15.24	23.08	28.08
16	17.78	25.62	30.62
20	22.86	30.70	35.70
24	27.94	35.78	40.78
26	30.48	38.32	43.32
30	35.56	43.40	48.40
34	40.64	48.48	53.48
40	48.26	56.10	61.10
50	60.96	68.80	73.80

(RoHS Compliant) **BF11 - XX B 0 GR X 000 C**  
 1 2 3 4 5 6 7

- 1. Circuits: 10~50 pin
- 2. B= With Ear
- 3. 2= W/O SR
- 3= With SR
- 4. Color: BK=Black  
GR=Rroy
- 5. Contact Plated:  
T=Matte Tin over Nickel  
W=Matte Tin over Nickel 150u"  
Y=Bright Tin over Nickel  
C=Gold Flash  
F=Gold Flash, Tin 50u"  
A=Gold 3u"  
B=Gold 3u", Ni 50u"
- 6. Special Options  
D=Gold 5u"  
E=Gold 5u", Ni 50u"  
G=Gold 10u"  
J=Gold 10u", Ni 50u"  
L=Gold 15u"  
M=Gold 15u", Ni 50u"  
U=Gold 30u"  
V=Gold 30u", Ni 50u"  
N=Gold Flash, Ni
- 7. Packing:  
C=Tray

①: Circuits: 06~64 pin-2008/10/07-C  
**CONN TOP COMPONENT INC.**  
 BOM 1:  
 2:  
 3:  
 TEL: (02)86481727 FAX: (02)86482427

PART NO	BF11-XXB0GRX000C	.X	.XX	.XXX
DRAWING NO	BF-00002	±0.3	±0.20	±0.100
DRAWN BY	GARY	EDITION: C1	ITEM: BF	SCALE: 1:1
APPROVAL BY				UNIT: m.m