



SPECIFICATION:
CONTACT RESISTANCE: 30M OHM MAX
30M OHM MAX
INSULATOR RESISTANCE:
1000M OHM MIN. AT DC 500V
CURRENT RATING: 1AM
DIELECTRIV WITHSTANDING VOL TAGE
AC 500V FOR 1 MINUTE
OPERATING TEMPERATURE:
-40°C ~+105°C
CONTACT MATERIAL: BRASS
INSULATOR MATERIAL:
P B T & 30% GLASS FIBER UL 94V-0

PART NO	A	B	C
10	10.16	18.16	22.96
14	15.24	23.08	28.08
16	17.78	25.62	30.62
20	22.86	30.70	35.70
24	27.94	35.78	40.78
26	30.48	38.32	43.32
30	35.56	43.40	48.40
34	40.64	48.48	53.48
40	48.26	56.10	61.10
50	60.96	68.80	73.80

(RoHS Compliant) **BF11 - XX N 0 GR X 000 C**

- Circuits: 10~50 pin
- N= W/O Ear
- 2= W/O SR
- Color: BK=Black
GR=Rroy
- Contact Plated:
T=Matte Tin over Nickel
W=Matte Tin over Nickel 150u"
Y=Bright Tin over Nickel
C=Gold Flash
F=Gold Flash, Tin 50u"
A=Gold 3u"
B=Gold 3u", Ni 50u"
- Special Options
D=Gold 5u"
E=Gold 5u", Ni 50u"
G=Gold 10u"
J=Gold 10u", Ni 50u"
L=Gold 15u"
M=Gold 15u", Ni 50u"
U=Gold 30u"
V=Gold 30u", Ni 50u"
N=Gold Flash , Ni
- Packging:
C=Troy

1 2 3 4 5 6 7

@:Circuits: 10~50 pin-2008/04/02-C1
 Q:BF11-XXN0GRX000-2007/11/09-C

CONN TOP COMPONENT INC.		PART NO		BF11-XXN0GRX000C	X	.XX	.XXX
DRAWING NO		BF-00001	EDITION:	C2	±0.3	±0.20	±0.100
DRAWN BY		GARY	2008/11/14				ITEM: BF
APPROVAL BY							SCALE: 1:1
							UNIT: m.m

TEL:(02)86481727 FAX:(02)86482427