



Current Rating: 3 Amps
Insulator Resistance: 5000 Megohms min
Contact Resistance: 20m ohms max.
Dielectric Withstanding: 1000V AC
Operating Temperature: -40° ~ +105° C
Max Processing Temp: 230° C for 60 seconds
Contact Material: Copper Alloy
Insulator Material: Polyester, UL 94V-0
Standard: Nylon-6T

Finish: Tin, Gold Plated
Standard: Gold Flash all over

**Recommended P.C. Board
 SMD Layout**

(RoHS Compliant)

- Insulator Material: N= Nylon-6T
- A=Phosphor Bronze
B= Brass
- Circuits: 06~64 pin
D0= S.M.D W/O Peg
5. Color: BK=Black
- Contact Plated: T=Matte Tin over Nickel
W=Matte Tin over Nickel
Y=Bright Tin over Nickel
C=Gold Flash
F=Gold Flash, Matte Tin 100u"
A=Gold 3u"
B=Gold 3u", Matte Tin 100u"
- E=Gold 5u", Matte Tin 100u"
G=Gold 10u"
J=Gold 10u", Matte Tin 100u"
L=Gold 15u"
M=Gold 15u", Matte Tin 100u"
U=Gold 30u"
V=Gold 30u", Matte Tin 100u"
- Packing: C=Tray

BH16 N X - XX D0 BK X 000 C

1 2 3 4 5 6 7 8



CONN TOP
COMPONENT INC.

1: BH16N-XXBKH0
2: QT-0.64X13.50BN
3:

PART NO

BH16NX-XXD0BKX000C

.X
±0.3

DRAWING NO

BH-00128

EDITION: C1

.XX
±0.20

DRAWN BY

LIN

2008/04/11

ITEM: BH

TEL:(02)86481727 FAX:(02)86482427

APPROVAL BY

SCALE: 1:1

UNIT: m.m