



Recommended P.C. Board
SMD Layout

Current Rating: 3 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20m ohms max.
 Dielectric Withstanding: 1000V AC
 Operating Temperature: -40° ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 Contact Material: Copper Alloy
 Insulator Material: Polyester, UL 94V-0
 Standard: Nylon-6T

Finish: Tin, Gold Plated

Standard: Gold Flash all over

(RoHS Compliant)

BH17 N X - 10 S0 BK X 000

1 2 3 4 5 6 7

1. Insulator Material: Nylon-6T
2. A=Phosphor Bronze
3. Circuits: 10pin
4. Tail Style: SO= Straight
5. Color: BK=Black
6. Contact Plated:
 - T=Matte Tin over Nickel
 - W=Matte Tin over Nickel 150u"
 - Y=Bright Tin over Nickel
 - C=Gold Flash
 - F=Gold Flash, Matte Tin 100u"
 - A=Gold 3u"
 - B=Gold 3u", Matte Tin 100u"
 - D=Gold 5u"
7. Special Options
 - E=Gold 5u", Matte Tin 100u"
 - G=Gold 10u"
 - J=Gold 10u", Matte Tin 100u"
 - L=Gold 15u"
 - M=Gold 15u", Matte Tin 100u"
 - U=Gold 30u"
 - V=Gold 30u", Matte Tin 100u"



CONN TOP
COMPONENT INC.

BOM 1:	BH12N-10BKHO
2:	QT-0.64X13.00BN
3:	

PART NO	BH17NX-10S0BKCE01	.X	.XX	.XXX
DRAWING NO	BH-00130	±0.3	±0.20	±0.100
DRAWN BY	LIN		ITEM: BH	
APPROVAL BY			SCALE: 1:1	
			UNIT: m.m	

TEL: (02)86481727 FAX: (02)86482427