



CONTACT	DIMENSION		
	A	B	C
06P	12.18	05.08	1.90
08P	14.72	07.62	1.90
10P	17.26	10.16	3.60
12P	19.80	12.70	3.60
14P	22.34	15.24	3.60
16P	24.88	17.78	3.60
18P	27.42	20.32	3.60
20P	29.96	22.86	3.60
24P	35.04	27.94	3.60
26P	37.58	30.48	3.60
30P	42.66	35.56	3.60
34P	47.74	40.64	3.60
40P	55.36	48.26	3.60
50P	68.06	60.96	3.60

MATERIALS:
 INSULATOR:P.B.T.30%GLASS FIBER, UL94V-0
 CONTACT MATERIAL:BRASS OR PHOSPHOR
 BRONZE,GOLD FLASH OVER NICKEL
ELECTRICAL:
 CURRENT RATING:1AMP DC
 INSULATION RESISTANCE:3000MΩ MIN.
 CONTACT RESISTANCE:30mΩ MAX.
 DIELECTRIC WITHSTANDING:500V AC
 OPERATING TEMPERATURE:-40°C~+105°C
 TERMINATED WITH 1.27mm PITCH FLAT RIBBON CABLE.

FC-11 - XX B0 BK N 000 X
 1 2 3 4 5 6

- Circuits: 06 to 50pin
- Material:
 - B0=Brass 4kg
 - B4=Brass 6kg
 - B6=Brass 6kg
 - P0=Phosphor Bronze 4kg
 - P4=Phosphor Bronze 6kg
 - P6=Phosphor Bronze 6kg
 - Color: BK=Black GR=Gray
- Contact Plated:
 - T=Matte Tin over Nickel
 - W=Matte Tin over Nickel 150u"
 - Y=Bright Tin over Nickel
 - C=Gold Flash
 - F=Gold Flash,Tin 100u"
 - A=Gold 3u"
 - B=Gold 3u",Ni 50u"
- Special Options
 - D=Gold 5u"
 - E=Gold 5u",Ni 50u"
 - G=Gold 10u"
 - J=Gold 10u",Ni 50u"
 - L=Gold 15u"
 - M=Gold 15u",Ni 50u"
 - U=Gold 30u"
 - V=Gold 30u",Ni 50u"
 - N=Gold Flash, Ni
- Packing:
 - C= Tray
 - N= Top & Reel

③:36P&44P-Delete-2008/09/30-C4
 ②:FC-11-XXB0BK N000-2008/01/14-C3
 ③:3.55-2007/12/11-C2
 ②:A-2007/10/01-C1
 ①:3.60-2007/04/23-C

CONN TOP COMPONENT INC.		PART NO		FC-11-XXB0BK N000X	.X	.XXX
①: FC-11-XXGRH0		DRAWING NO		FC-00069	±0.3	±0.100
②: FC-14-XXGRM0		DRAWN BY		GARY	EDITION: C6	ITEM: FC
③: FCT-B		APPROVAL BY			2009/04/09	SCALE: 1:1
TEL:(02)86481727 FAX:(02)86482427						UNIT: m.m