



CONTACT	DIMENSION			
	A	B	C	D
06P	12.18	05.08	13.10	1.90
08P	14.72	07.62	13.10	1.90
10P	17.26	10.16	13.35	3.60
12P	19.80	12.70	13.35	3.60
14P	22.34	15.24	13.35	3.60
16P	24.88	17.78	13.35	3.60
18P	27.42	20.32	13.55	3.60
20P	29.96	22.86	13.35	3.60
24P	35.04	27.94	13.35	3.60
26P	37.58	30.48	13.35	3.60
30P	42.66	35.56	13.35	3.60
34P	47.74	40.64	13.35	3.60
40P	55.36	48.26	13.35	3.60
50P	68.06	60.96	13.35	3.60

MATERIALS:
 INSULATOR:P.B.T.30%GLASS FIBER, UL94V-0
 CONTACT MATERIAL:BRASS OR PHOSPHOR
 BRONZE,GOLD FLASH OVER NICKEL
ELECTRICAL:
 CURRENT RATING:1AMP DC
 INSULATION RESISTANCE:3000MΩ MIN.
 CONTACT RESISTANCE:30mΩ MAX.
 DIELECTRIC WITHSTANDING:500V AC
 OPERATING TEMPERATURE:-40°C~+105°C
 TERMINATED WITH 1.27mm PITCH FLAT RIBBON CABLE.

FC - 113 - XX B0 BK N 000 C
 1 2 3 4 5 6

- (RoHS Compliant)
- Circuits: 06 to 50pin
 - Material:
 B0=Brass 4kg
 B4=Brass 6kg
 B6=Brass 6kg
 P0=Phosphor Bronze 4kg
 P4=Phosphor Bronze 6kg
 Color: BK=Black
 GR=Grey
 - Contact Plated:
 T=Matte Tin over Nickel
 W=Matte Tin over Nickel 150u"
 Y=Brighe Tin over Nickel
 C=Gold Flash
 F=Gold Flash,Matte Tin 100u"
 A=Gold 3u"
 B=Gold 3u",Ni 50u"
 D=Gold 5u"
 - Special Options
 - Packing: C= Troy

- E=Gold 5u",Ni 50u"
- G=Gold 10u"
- J=Gold 10u",Ni 50u"
- L=Gold 15u"
- M=Gold 15u",Ni 100u"
- U=Gold 30u"
- V=Gold 30u",Ni 50u"
- N=Gold Flash , Ni
- Special Options
- Packing: C= Troy

④:3.55-2007/12/11-C3	③:3.60-2007/09/14-C1	②:12.80-2007/04/23-C	①:3.6P&44P-Delete-2008/09/30-C5	⑤:FC-113-XXB0BK N000-2008/01/14-C4
CONN TOP COMPONENT INC.				
PART NO FC-113-XXB0BK N000C				
DRAWING NO FC-00077	EDITION: C6	X ±0.3	.XX ±0.20	.XXX ±0.100
DRAWN BY GARY	2009/04/06	SCALE: 1:1	ITEM: FC	UNIT: m.m
APPROVAL BY				

1: FC-14-XXBKM10
 2: FC-13-XXBKSJR
 3: FC-11-XXGRH0 4: FCT-B

TEL:(02)86481727 FAX:(02)86482427