



CONTACT	DIMENSION					
	A	B	C	A	B	C
06P	12.18	05.08	13.10	29.96	22.86	13.35
08P	14.72	07.62	13.10	35.04	27.94	13.35
10P	17.26	10.16	13.35	37.58	30.48	13.35
12P	19.80	12.70	13.35	42.66	35.56	13.35
14P	22.34	15.24	13.35	47.74	40.64	13.35
16P	24.88	17.78	13.35	55.36	48.26	13.35
18P	27.42	20.32	13.55	68.06	60.96	13.35

MATERIALS:
 INSULATOR:P.B.T.30%GLASS FIBER, UL94V-0
 CONTACT MATERIAL:BRASS OR PHOSPHOR
 BRONZE,GOLD FLASH OVER NICKEL
ELECTRICAL:
 CURRENT RATING:1AMP DC
 INSULATION RESISTANCE:3000MΩ MIN.
 CONTACT RESISTANCE:30mΩ MAX.
 DIELECTRIC WITHSTANDING:500V AC
 OPERATING TEMPERATURE:-40°C~+105°C
 TERMINATED WITH 1.27mm PITCH FLAT RIBBON CABLE.

FC-123 - XX B0 BK N 000 C
 1 2 3 4 5 6

- Circuits: 06 to 50pin
- Material:
 B0=Brass 4kg
 B4=Brass 6kg
 B6=Brass 6kg
 P0=Phosphor Bronze 4kg
 P4=Phosphor Bronze 4kg
 P6=Phosphor Bronze 6kg
 Color: BK=Black
 GR=Grey
- Contact Plated:
 T=Matte Tin over Nickel
 W=Matte Tin over Nickel 150u"
 Y=Brighte Tin over Nickel
 C=Gold Flash
 F=Gold Flash,Matte Tin 100u"
 A=Gold 3u"
 B=Gold 3u",Ni 100u"
 D=Gold 5u"
- Special Options
 Packing: C=Tray

①:FC-123-XXB0BK N000X-2008/01/14-C3		③:36P&44P-Delete-2009/02/18-C4	
③:3.55-2007/12/14-C2		④:36P&44P-Delete-2009/02/18-C4	
②:A-2007/09/14-C1		⑤:36P&44P-Delete-2009/02/18-C4	
①:12.80-2007/04/23-C		⑥:36P&44P-Delete-2009/02/18-C4	
CONN TOP COMPONENT INC.		PART NO	FC-123-XXB0BK N000C
1: FC-14-XXBKM0		DRAWING NO	FC-00081
2: FC-13-XXBKS R		DRAWN BY	GARY
3: FC-12-XXGRH0 4: FCT-B		EDITION:	C5
TEL:(02)86481727 FAX:(02)86482427		SCALE:	1:1
		APPROVAL BY	
		UNIT:	m.m

(RoHS Compliant)