



2.54\*(No. of Contacts/2-1)

FC-17Y - XX B0 BK N 000  
 1 2 3 4 5

(RoHS Compliant)

1. Circuits: 10 to 64pin

2. Material:

- B0=Brass 4kg
- B4=Brass 6kg
- B6=Brass 6kg
- P0=Phosphor Bronze 4kg
- P4=Phosphor Bronze 6kg
- P6=Phosphor Bronze 4kg

4. Contact Plated:

- T=Matte Tin over Nickel
- W=Matte Tin over Nickel 150u"
- Y=Brighe Tin over Nickel
- C=Gold Flash
- F=Gold Flash, Tin 100u"
- A=Gold 3u"
- B=Gold 3u", Ni 50u"
- D=Gold 5u"

E=Gold 5u", Ni 50u"

G=Gold 10u"

J=Gold 10u", Ni 50u"

L=Gold 15u"

M=Gold 15u", Ni 50u"

U=Gold 30u", Ni 50u"

V=Gold 30u", Ni 50u"

N=Gold Flash, Ni

5. Special Options

GR=Grey

**MATERIALS:**  
 INSULATOR:P.B.T.30%GLASS FIBER,UL94V-0  
 CONTACT MATERIAL:BRASS OR PHOSPHOR  
 BRONZE,GOLD FLASH OVER NICKEL  
**ELECTRICAL:**  
 CURRENT RATING:1AMP.  
 INSULATION RESISTANCE:1000M Ω MIN.  
 CONTACT RESISTANCE:30m Ω MAX  
 DIELECTRIC WITHSTANDING:500VAC  
 OPERATING TEMPERATURE:-40°C~+85°C



CONN TOP  
 COMPONENT INC.

PART NO	FC-17Y-XXXB0BKNN000	X	.X
DRAWING NO	2540-00022	±0.2	.XX
DRAWN BY	GARY	C	±0.2
EDITION:	2007/04/23		ITEM: 2540
SCALE:	1:1		SCALE: 1:1
UNIT:	m.m		

TEL: (02)86481727 FAX: (02)86482427

APPROVAL BY

UNIT: m.m