



(RoHS Compliant)

HI N 17 X - 1 XX D0 BK X 000 X
1 2 3 4 5 6 7 8

- Insulator Material: N = Nylon-6T, P = Phosphor Bronze, Blank=Brass, 3. Per Row: 03 to 40, 4. Tail Style: DA = S.M.D A Type, DB = S.M.D B Type, 5. Color: BK=Black, WH=White
- Contact Plated: T=Matte Tin over Nickel, W=Matte Tin over Nickel 150u", Y=Bright Tin over Nickel, C=Gold Flash, F=Gold Flash, Matte Tin 100u", A=Gold 3u", B=Gold 3u", Matte Tin 100u"
- Special Options: 8. Packings: B = Tube, D = Box

①:HINI17-1XXXD0BKX000-2007/01/24-C



CONN TOP
COMPONENT INC.

1: HINI17-1XXXBKH0
BOM 2: QT-0.64X11.00BN
3: 0

PART NO	HINI17X-1XXXD0BKX000X	.X	.XX	.XXX
DRAWING NO	PH-00127	±0.3	±0.20	±0.100
DRAWN BY	GARY	EDITION: C1	SCALE: 1:1	ITEM: PH
APPROVAL BY		2008/05/27		UNIT: m.m

Finish: Tin, Gold Plated
Standard: Gold Flash all over

Current Rating: 3 Amps
Insulator Resistance: 5000 Megohms min
Contact Resistance: 20 m ohms max
Dielectric Withstanding: 1000 V AC
Operating Temperature: -40° ~ +105° C
Max Processing Temp: 230° C for 60 seconds
Max Processing Temp: 260° C for 10 seconds
Contact Material: Copper Alloy
Insulator Material: Polyester, UL 94V-0
Standard: Nylon-6T