



**Current Rating:** 3 Amps  
**Insulator Resistance:** 5000 Megohms min  
**Contact Resistance:** 20 m ohms max  
**Dielectric Withstanding:** 1000 V AC  
**Operating Temperature:** -40° ~ +105° C  
**Max Processing Temp:** 230° C for 60 seconds  
**Max Processing Temp:** 260° C for 10 seconds  
**Contact Material:** Copper Alloy  
**Insulator Material:** Polyester, UL 94V-0  
**Standard:** Nylon-6T

**Finish:** Tin, Gold Plated  
**Standard:** Gold Flash all over

- (RoHS Compliant)
1. Insulator Material: N = Nylon-6T  
 2. P = Phosphor Bronze  
 Blank=Brass  
 3. Per Row: 02 to 40  
 4. Tail Style: SO = Straight  
 5. Color: BK=Black  
 WH=White
6. Contact Plated: T=Matte Tin over Nickel  
 W=Matte Tin over Nickel  
 Y=Bright Tin over Nickel  
 C=Gold Flash  
 F=Gold Flash,Matte Tin  
 A=Gold 3u"  
 B=Gold 3u",Matte Tin
7. Special Options: D=Gold 5u"  
 E=Gold 5u",Matte Tin  
 G=Gold 10u"  
 J=Gold 10u",Matte Tin  
 L=Gold 15u"  
 M=Gold 15u",Matte Tin  
 U=Gold 30u"  
 V=Gold 30u",Matte Tin
8. Packing: A = PE Bog  
 D = Box
- HI N 17 X - 2 XX S0 BK X 000 X  
 1 2 3 4 5 6 7 8

CONN TOP COMPONENT INC. ①:HIN17-2XXXS0BKX000-2007/01/24-C		PART NO	HIN17X-2XXXS0BKX000X	.X	.XX	.XXX
1:	HIN17-2XXXBKH0	DRAWING NO	PH-00132	EDITION:	C1	ITEM: PH
2:	QT-0.64X10.80BN	DRAWN BY	GARY	2008/05/27	SCALE: 1:1	
3:	0	APPROVAL BY				UNIT: m.m
TEL:(02)86481727 FAX:(02)86482427						