



(RoHS Compliant)

H2 N 15 X - 2 XX SK BK X 001 X
1 2 3 4 5 6 7 8

- Insulator Material:
N= Nylon-6T
P= Phosphor Bronze
Blank= Brass
3. Per Row 02~40 pin
4. Tail Style:
SK= Straight W/Kink
5. Color: BK=Black
WH=White
- Contact Plated:
T=Matte Tin over Nickel
W=Matte Tin over Nickel 150u"
Y=Bright Tin over Nickel
C=Gold Flash
F=Gold Flash,Matte Tin 100u"
A=Gold 3u"
B=Gold 3u",Matte Tin 100u"
- Special Options:
D=Gold 5u"
E=Gold 5u",Matte Tin 100u"
G=Gold 10u"
J=Gold 10u",Matte Tin 100u"
L=Gold 15u"
M=Gold 15u",Matte Tin 100u"
U=Gold 30u"
V=Gold 30u",Matte Tin 100u"
- Packaging:
A= PE Bag
D= Box



CONN TOP
COMPONENT INC.

①:H2N15-2XXXSKBKX001-2007/01/25-C

PART NO H2N15X-2XXXSKBKX001X

X .X
±0.3 ±0.100

DRAWING NO

PHA-00111

EDITION: C1

ITEM: PHA

DRAWN BY

GARY

2008/05/15

SCALE: 1:1

APPROVAL BY

UNIT: m.m

Current Rating: 2 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: -40° ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 Max Processing Temp: 260° C for 10 seconds
 Contact Material: Copper Alloy
 Insulator Material: Polyester, UL 94V-0
 Standard: Nylon-6T
 Finish: Tin, Gold Plated
 Standard: Gold Flash all over

Recommended P.C. Board
 Hole Layout