



Recommended P.C. Board
SMD Layout

Current Rating: 2 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: -40° ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 Max Processing Temp: 260° C for 10 seconds
 Contact Material: Copper Alloy
 Insulator Material: Polyester, UL 94V-0
 Standard: Nylon-6T
 Finish: Tin, Gold Plated
 Standard: Gold Flash all over

(RoHS Compliant) H2 N 15 X - 2 XX D0 BK X D04 X
 1 2 3 4 5 6 7 8

- Insulator Material:
 N= Nylon-6T
 P= Phosphor Bronze
 Blank= Brass
 3. Per Row 02~40 pin
 4. Tail Style:
 D0= S.M.D Type
 5. Color: BK=Black
 WH=White
- Contact Plated:
 T=Matte Tin over Nickel
 W=Matte Tin over Nickel 150u"
 Y=Bright Tin over Nickel
 C=Gold Flash
 F=Gold Flash,Matte Tin 100u"
 A=Gold 3u"
 B=Gold 3u",Matte Tin 100u"
- D=Gold 5u"
 E=Gold 5u",Matte Tin 100u"
 G=Gold 10u"
 J=Gold 10u",Matte Tin 100u"
 L=Gold 15u"
 M=Gold 15u",Matte Tin 100u"
 U=Gold 30u"
 V=Gold 30u",Matte Tin 100u"
- Special Options
 8. Packings:
 A= PE Bog
 B =Tube
 D= Box

		PART NO		H2N15X-2XXXD0BKXD04X		.X		.XXX	
1: H2N15-2XXXBKH0 2: QT-0.50X9.50BN 3: 0		DRAWING NO		PHA-00268		EDITION: C		ITEM: PHA	
TEL: (02)86481727 FAX: (02)86482427		DRAWN BY		GARY		2008/10/15		SCALE: 1:1	
APPROVAL BY								UNIT: m.m	