



Recommended P.C. Board
Hole Layout

Current Rating: 2 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: -40 ~ +105° C
 Contact Material: Copper Alloy
 Insulator Material: Polyester, UL 94V-0 Standard: PBT
 Finish: Tin, Gold Plated
 Standard: Gold Flash all over
 Note: Duplex Plating: Gold Plated on contact area, Tin on solder area

Max Processing Temp: 230° C for 60 seconds
 Max Processing Temp: 260° C for 10 seconds
 Insulator Material: Polyester, UL 94V-0 Standard: Nylon-6T

(RoHS Compliant) H2 X 70 X - 2 25 R0 BK X E01 X

- Insulator Material:
 - A= P.B.T
 - N= Nylon-6T
 - P= Phosphor Bronze
 - Blank= Brass
 - 2. Circuits: 50 pin
 - 3. Tails Style:
 - RO= Right Angle
 - Color: BK=Black
 - WH=White
- Contact Plated:
 - T=Matte Tin over Nickel
 - W=Matte Tin over Nickel 150u"
 - Y=Bright Tin over Nickel
 - C=Gold Flash
 - F=Gold Flash,Matte Tin 100u"
 - A=Gold 3u"
 - B=Gold 3u",Matte Tin 100u"
6. E01=25,45,46 Not insert pin
7. Packing:
 - A= PE Bog
 - B= Tube
 - D= Box



CONN TOP
COMPONENT INC.

①:H2X70-225R0BKXE01-2007/02/27-C

1:	H2X70-2XXXBKH0
BOM 2:	QT-0.50X 11.50BN
3:	QT-0.50X 15.50BN

TEL:(02)86481727 FAX:(02)86482427

PART NO	H2X70X-225R0BKXE01X	.X	.XX	.XXX
DRAWING NO	PHA-00049	±0.3	±0.20	±0.100
DRAWN BY	GARY	EDITION: C1	SCALE: 1:1	ITEM: PHA
APPROVAL BY				UNIT: m.m