



Current Rating: 1 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: -40° ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 Max Processing Temp: 260° C for 10 seconds
 Contact Material: Copper Alloy
 Insulator Material: Polyester, UL 94V-0
 Finish: Tin, Gold Plated
 Standard: Gold Flash all over
 Standard: Nylon-6T

Recommended P.C. Board
 SMD Layout

(RoHS Compliant) H3 N 10 X - 2 XX D3 BK X 001 B
 1 2 3 4 5 6 7 8

- Insulator Material:
N = Nylon-6T
- P = Phosphor Bronze
Blank=Brass
- Per Row 03-50 pin
- Tail Style:
D3 = S.M.D With Peg Type
Ø0.70x0.85mm
- Color: BK=Black
WH=White
- Contact Plated:
C=Gold Flash
A=Gold 3u"
D=Gold 5u"
G=Gold 10u"
L=Gold 15u"
U=Gold 30u"
- Special Options
B = Tube
- Packaging:
B = Tube

©:H3N10-2XXD3BKX001-2007/06/28-C1		CONN TOP COMPONENT INC.		PART NO	H3N10X-2XXD3BKX001B	X	.XX	.XXX
①:H3N10-2XXD3BKX000-2007/05/11-C		DRAWING NO		PHB-00152	EDITION: C2	±0.3	±0.20	±0.100
TEL: (02)86481727 FAX: (02)86482427		DRAWN BY		GARY	2009/01/19	SCALE: 1:1		UNIT: m.m
		APPROVAL BY						