



Current Rating: 1 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: -40° ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 Max Processing Temp: 260° C for 10 seconds
 Contact Material: Phosphor Bronze
 Insulator Material: Polyester, UL 94V-0
 Standard: Nylon-6T
 Finish: Tin, Gold Plated
 Standard: Gold Flash all over

Recommended P.C. Board
Hole Layout

(RoHS Compliant) H3 N 10 X - 1 XX S0 BK X D01 X
 1 2 3 4 5 6 7 8

- Insulator Material: N = Nylon-6T
- Phosphor Bronze: Blank=Brass
- Per Row 02~50 pin
- Tail Style: SO = Straight
- Color: BK=Black, WH=White
- Contact Plated: G=Gold Flash, A=Gold 3u", D=Gold 5u", G=Gold 10u", L=Gold 15u", U=Gold 30u"
- Special Options: A = PE Bog, D = Box
- Packing: A = PE Bog, D = Box

CONN TOP COMPONENT INC. ①:H3N10-1XXXS0BKXD01-2007/02/13-C		PART NO		H3N10X-1XXXS0BKXD01X		.X		.XX		.XXX	
BOM 1: H3N10-1XXXBKHO		DRAWING NO		PHB-00078		EDITION: C1		ITEM: PHB			
BOM 2: QT-0.40X8.90BN		DRAWN BY		GARY		2009/01/19		SCALE: 1:1			
BOM 3: 0		APPROVAL BY						UNIT: m.m			
TEL:(02)86481727 FAX:(02)86482427											