



Current Rating: 1 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: -40° ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 Max Processing Temp: 260° C for 10 seconds
 Contact Material: Phosphor Bronze
 Insulator Material: Polyester, UL 94V-0
 Standard: Nylon-6T
 Finish: Tin, Gold Plated
 Standard: Gold Flash all over

Recommended P.C. Board Hole Layout

(RoHS Compliant) H3 N 10 A X - 2 XX S0 BK X D01 X
 1 1 2 3 4 5 6 7 8

- Insulator Material:
N = Nylon-6T
- Phosphor Bronze
Blank = Brass
- Per Row 02~50 pin
- Tail Style:
S0 = Straight
- Contact Plated:
C = Gold Flash
A = Gold 3u"
D = Gold 5u"
G = Gold 10u"
L = Gold 15u"
U = Gold 30u"
- Special Options
A = PE Bag
D = Box



CONN TOP
COMPONENT INC.

©:H3N10A-2XXS0BKXD01-2007/09/29-C

1:	H3N10A-2XXS0BKXH0
2:	QT-0.46X6.200BN
3:	0

BOM

TEL: (02)86481727 FAX: (02)86482427

PART NO	H3N10AX-2XXS0BKXD01X	.X	.XX	.XXX
DRAWING NO	PHB-00166	±0.3	±0.20	±0.100
DRAWN BY	GARY	EDITION: C1	ITEM: PHB	SCALE: 1:1
APPROVAL BY				UNIT: m.m