



Current Rating: 1 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: -40° ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 Max Processing Temp: 260° C for 10 seconds
 Contact Material: Phosphor Bronze
 Insulator Material: Polyester, UL 94V-0
 Standard: Nylon-6T
 Finish: Tin, Gold Plated
 Standard: Gold Flash all over

Recommended P.C. Board
 Hole Layout

Part No.	Dim.A ±0.20	Dim.B ±0.20
H3N15X-1XXXS0BKX0001X	2.60mm	3.00mm
H3N15X-1XXXS0BKX0002X	2.60mm	1.80mm
H3N15X-1XXXS0BKX0003X	1.50mm	3.00mm
H3N15X-1XXXS0BKX0004X	1.50mm	1.80mm

(RoHS Compliant) H3 N 15 X - 1 XX S0 BK X 000 X
 1 2 3 4 5 6 7 8

- Insulator Material:
 - N = Nylon-6T
- Insulator Material:
 - S0 = Straight
- Contact Plated:
 - C=Gold Flash
 - A=Gold 3u"
 - D=Gold 5u"
 - G=Gold 10u"
 - L=Gold 15u"
 - U=Gold 30u"
- Tail Style:
 - A = PE Bog
 - B = Tube
 - D = Box
- Special Options:
 - Blank=Brass
 - Color: BK=Black
 - WH=White
- Per Row 02~50 pin



CONN TOP
 COMPONENT INC.

Ⓢ:H3N15-1XXXS0BKX000-2007/02/27-C

1:	H3N15-1XXXBKHO
2:	QT-0.40X XXXBN
3:	0

PART NO	H3N15X-1XXXS0BKX000X	X	.XX	.XXX
DRAWING NO	PHB-00065	±0.3	±0.20	±0.100
DRAWN BY	GARY	EDITION: C1	ITEM: PHB	SCALE: 1:1
APPROVAL BY			UNIT: m.m	

TEL: (02)86481727 FAX: (02)86482427