



Current Rating: 1 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: -40° ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 Max Processing Temp: 260° C for 10 seconds
 Contact Material: Phosphor Bronze
 Insulator Material: Polyester, UL 94V-0
 Finish: Tin, Gold Plated
 Standard: Gold Flash all over
 Standard: Nylon-6T

Recommended P.C. Board
 Hole Layout

1.27 * No. of Contacts / 2 - 1.27

Part No.	Dim.A ±0.20	Dim.B ±0.20
H3N15X-2XXXS0BKX001X	2.60mm	3.00mm
H3N15X-2XXXS0BKX002X	2.60mm	1.80mm
H3N15X-2XXXS0BKX003X	1.50mm	3.00mm
H3N15X-2XXXS0BKX004X	1.50mm	1.80mm

(RoHS Compliant) H3 N 15 X - 2 XX S0 BK X 000 X

1 2 3 4 5 6 7 8

1. Insulator Material: 4. Tail Style: 6. Contact Plated: 7. Special Options

N = Nylon-6T SO = Straight C=Gold Flash A=Gold 3u" D=Gold 5u" G=Gold 10u" L=Gold 15u" U=Gold 30u"

2. P = Phosphor Bronze 5. Color: BK=Black WH=White A = PE Bog B = Tube

3. Per Row 02~50 pin D = Box



PART NO	H3N15X-2XXXS0BKX000X	X	±0.3	.XX	±0.20	.XXX	±0.100
DRAWING NO	PHB-00068	EDITION:	C1	ITEM:	PHB	SCALE:	1:1

1:	H3N15-2XXXBKHO	DRAWN BY	GARY	APPROVAL BY		UNIT:	m.m
2:	QT-0.40XXXBN						
3:	0						

TEL: (02)86481727 FAX: (02)86482427