



Current Rating: 1 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: - 40 ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 Max Processing Temp: 260° C for 10 seconds
 Contact Material: Copper Alloy
 Insulator Material: Polyester, UL 94V-0
 Standard: Nylon-6T
 Finish: Tin, Gold Plated
 Standard: Gold Flash all over

Recommended P.C. Board
 SMD Layout

(RoHS Compliant) H3 N 15 X - 2 XX D1 BK X D02 X
 1 2 3 4 5 6 7 8

- Insulator Material:
N = Nylon-6T
- P = Phosphor Bronze
Blank = Brass
- Per Row 03~50 pin
- Tail Style:
D1 = S.M.D With Peg Type
- Color: BK = Black
WH = White
- Contact Plated:
C = Gold Flash
A = Gold 3u"
D = Gold 5u"
G = Gold 10u"
L = Gold 15u"
U = Gold 30u"
- Special Options
E = CAP + Tap & Reel
F = CAP + Tube
G = CAP + Tray
H = CAP + Bag
- Packaging:
E = CAP + Tap & Reel
F = CAP + Tube
G = CAP + Tray
H = CAP + Bag

②:CAP-H32-03-2008/07/21-C ①:Dim.A 5.84-2008/07/21-C			
PART NO	H3N15X-2 XXD1BKXD02X	X	.XXX
DRAWING NO	PHB-00201	±0.3	±0.20
DRAWN BY	GARY	EDITION: C1	ITEM: PHB
APPROVAL BY		2008/08/21	SCALE: 1:1
			UNIT: m.m
TEL: (02)86481727 FAX: (02)86482427		BOM 1: H3N15-2XXXBKHH0 2: H3N15-2XXXBKHH 3: QT-0.40X12.50BN 4: ②:CAP-H32-02	