


Current Rating: 1 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: -40° ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 Max Processing Temp: 260° C for 10 seconds
 Contact Material: Phosphor Bronze
 Insulator Material: Polyester, UL 94V-0
 Finish: Tin, Gold Plated
 Standard: Gold Flash all over
 Standard: Nylon-6T

Recommended P.C. Board Hole Layout



Part No.	Dim.A ±0.20	Dim.B ±0.20
H3N15AX-2XXXS0BKX001X	2.60mm	3.00mm
H3N15AX-2XXXS0BKX002X	2.60mm	1.80mm
H3N15AX-2XXXS0BKX003X	1.50mm	3.00mm
H3N15AX-2XXXS0BKX004X	1.50mm	1.80mm

(RoHS Compliant) H3 N 15 A X - 2 XX S0 BK X 000 X
 1 2 3 4 5 6 7 8

- Insulator Material: N= Nylon-6T
- P= Phosphor Bronze
Blank=Brass
- Per Row 02~50 pin
- Tail Style: S0= Straight
- Color: BK=Black
WH=White
- Contact Plated: C=Gold Flash
A=Gold 3u"
D=Gold 5u"
G=Gold 10u"
L=Gold 15u"
U=Gold 30u"
- Special Options: A= PE Bag
B= Tube
D= Box
- Packing:

©:H3N15A-2XXXS0BKX000-2007/02/27-C			
CONN TOP COMPONENT INC.		PART NO	H3N15AX-2XXXS0BKX000X
1: H3N15A-2XXXBKHX0	DRAWING NO	PHB-00081	EDITION: C1
2: QT-0.46X7.10BN	DRAWN BY	GARY	2009/02/03
3: 0	APPROVAL BY		
TEL: (02)86481727	FAX: (02)86482427		
		X	.XX
		±0.3	±0.20
			±0.100
		ITEM: PHB	SCALE: 1:1
		UNIT: m.m	