



Part No.	Dim.A ±0.20	Dim.B ±0.20
H3N17X-2XXS0BKX001X	2.60mm	3.00mm
H3N17X-2XXS0BKX002X	2.60mm	1.80mm
H3N17X-2XXS0BKX003X	1.50mm	3.00mm
H3N17X-2XXS0BKX004X	1.50mm	1.80mm

(RoHS Compliant) H3 N 17 X - 2 XX S0 BK X 000 X
 1 2 3 4 5 6 7 8

- Insulator Material:
N = Nylon-6T
- P = Phosphor Bronze
Blank=Brass
- Per Row 02~50 pin
- Tail Style:
SO = Straight
- Contact Plated:
G=Gold Flash
A=Gold 3u"
D=Gold 5u"
G=Gold 10u"
L=Gold 15u"
U=Gold 30u"
- Special Options:
A = PE Bag
B = Tube
D = Box

Current Rating: 1 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: -40° ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 Max Processing Temp: 260° C for 10 seconds
 Contact Material: Phosphor Bronze
 Insulator Material: Polyester, UL 94V-0
 Standard: Nylon-6T
 Finish: Tin, Gold Plated
 Standard: Gold Flash all over

Recommended P.C. Board
 Hole Layout

©:H3N17-2XXS0BKX000-2007/03/29-C

CONN TOP COMPONENT INC.		PART NO	H3N17X-2XXS0BKX000X	.X	±0.3	.XX	±0.20	.XXX	±0.100
1:	H3N17-2XXBKH0	DRAWING NO	PHB-00145	EDITION:	C1	ITEM:	PHB		
2:	QT-0.40X XXXBN	DRAWN BY	GARY	2009/02/04	SCALE:	1:1	UNIT:	m.m	
3:	0	APPROVAL BY							

TEL: (02)86481727 FAX: (02)86482427