


Recommended P.C. Board
SMD Layout

Current Rating: 1 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: - 40° ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 Max Processing Temp: 260° C for 10 seconds
 Contact Material: Phosphor Bronze
 Insulator Material: Polyester, UL 94V-0
 Standard: Nylon-6T

Finish: Tin, Gold Plated
 Standard: Gold Flash all over

(RoHS Compliant) H3 N 25 X - 2 XX D0 BK X D10 X
 1 2 3 4 5 6 7 8

- Insulator Material: Nylon-6T
N = Nylon-6T
- P = Phosphor Bronze
Blank = Brass
- Per Row 02~50 pin
- Tail Style: DO=S.M.D No Peg Type
- Color: BK=Black
WH=White
- Contact Plated: C=Gold Flash
A=Gold 3u"
D=Gold 5u"
G=Gold 10u"
L=Gold 15u"
U=Gold 30u"
- Special Options: B = Tube
D = Box
- Packing: B = Tube
D = Box

 CONN TOP COMPONENT INC. TEL: (02)86481727 FAX: (02)86482427		PRT NO H3N25X-2XXD0BKXD10X DRAWING NO PHB-00189 DRAWN BY GARY APPROVAL BY		X ±0.3 XX ±0.20 XXX ±0.100	
1: H3N25-2XXBKHH0	2: H3N20-2XXBKHH0	3: QT-0.4*10.60BN	EDITION: C1	SCALE: 1:1	UNIT: m.m