



Recommended P.C. Board
Hole Layout

Current Rating: 1 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: -40° ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 Max Processing Temp: 260° C for 10 seconds
 Contact Material: Phosphor Bronze
 Insulator Material: Polyester, UL 94V-0
 Standard: Nylon-6T

(RoHS Compliant) H3 N 25 X - 2 XX S0 BK X D01 X
 1 2 3 4 5 6 7 8

- Insulator Material: Nylon-6T
- P = Phosphor Bronze
Blank = Brass
- Per Row 02~50 pin
- Tail Style: SQ = Straight
- Color: BK=Black
WH=White
- Contact Plated: G=Gold Flash
A=Gold 3u"
D=Gold 5u"
G=Gold 10u"
L=Gold 15u"
U=Gold 30u"
- Special Options: A = PE Bag
D = Box
- Packing:

1:	H3N25-2XXXBKXHD01X
2:	QT-0.40X15.40BN
3:	0
TEL: (02)86481727 FAX: (02)86482427	

PART NO	H3N25X-2XXXS0BKXD01X	.X	.XX	.XXX
DRAWING NO	PHB-00128	±0.3	±0.20	±0.100
DRAWN BY	LIN	EDITION: C1	SCALE: 1:1	ITEM: PHB
APPROVAL BY				UNIT: m.m