






1.27\*No.of Contacts±0.3



Current Rating: 1 Amps  
 Insulator Resistance: 5000 Megohms min  
 Contact Resistance: 20 m ohms max  
 Dielectric Withstanding: 500 V AC  
 Operating Temperature: -40° ~ +105° C  
 Max Processing Temp: 230° C for 60 seconds  
 Max Processing Temp: 260° C for 10 seconds  
 Contact Material: Phosphor Bronze  
 Insulator Material: Polyester; UL 94V-0  
 Standard: Nylon-6T  
 Finish: Tin, Gold Plated  
 Standard: Gold Flash all over

Recommended P.C. Board  
 Hole Layout

1.27\*No.of Contacts-1.27

Part No.	Dim.A ±0.20	Dim.B ±0.20
H3N25AX-1XXS0BKX001X	2.60mm	3.00mm
H3N25AX-1XXS0BKX002X	2.60mm	1.80mm
H3N25AX-1XXS0BKX003X	1.50mm	3.00mm
H3N25AX-1XXS0BKX004X	1.50mm	1.80mm

(RoHS Compliant) H3 N 25 A X - 1 XX S0 BK X 000 X  
 1 2 3 4 5 6 7 8

- Insulator Material:  
N= Nylon-6T
- Trail Style:  
S0= Straight
- Contact Plated:  
C=Gold Flash  
A=Gold 3u"  
D=Gold 5u"  
G=Gold 10u"  
L=Gold 15u"  
U=Gold 30u"
- Special Options:  
A= PE Bag  
B= Tube  
D= Box
- Phosphor Bronze  
Blank=Brass
- Color: BK=Black  
WH=White
- Per Row 02~50 pin



PART NO	H3N25AX-1XXS0BKX000X	.X	.XX	.XXX
DRAWING NO	PHB-00013	±0.3	±0.20	±0.100

1:	H3N25A-1XXBKHH0	DRAWN BY	GARY	EDITION:	C1	ITEM:	PHB
2:	QT-0.46X XXBN	SCALE:	1:1				
3:	0	UNIT:	m.m				

TEL: (02)86481727 FAX: (02)86482427