



(RoHS Compliant) H3 N 25 A X - 2 XX R0 BK X 000 X
 1 2 3 4 5 6 7 8

1. Insulator Material:

N = Nylon-6T

2. P = Phosphor Bronze

Blank=Brass

3. Per Row 02~50 pin

4. Tail Style:

RO = Right Angle

5. Color: BK=Black

WH=White

6. Contact Plated:

C=Gold Flash
 A=Gold 3u"
 D=Gold 5u"
 G=Gold 10u"
 L=Gold 15u"
 U=Gold 30u"

7. Special Options

A= PE Bag
 B= Tube
 D= Box



CONN TOP
 COMPONENT INC.

①:H3N25A-2XXR0BKX000-2007/02/27-C

Part No.	Dim.A ±0.20	Dim.B ±0.20	Dim.C ±0.20
H3N25AX-2XXR0BKX001X	2.60mm	3.00mm	3.30mm
H3N25AX-2XXR0BKX002X	2.60mm	1.80mm	3.30mm
H3N25AX-2XXR0BKX003X	1.50mm	3.00mm	3.30mm
H3N25AX-2XXR0BKX004X	1.50mm	1.80mm	3.30mm

Recommended P.C. Board
 Hole Layout

Current Rating: 1 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: -40° ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 Max Processing Temp: 260° C for 10 seconds
 Contact Material: Phosphor Bronze
 Insulator Material: Polyester, UL 94V-0
 Standard: Nylon-6T

PART NO		H3N25AX-2XXR0BKX000X		.X	.XX	.XXX
DRAWING NO		PHB-00051		±0.3	±0.20	±0.100
DRAWN BY		GARY		EDITION: C1	ITEM: PHB	
APPROVAL BY				2009/02/13	SCALE: 1:1	
TEL: (02)86481727 FAX: (02)86482427					UNIT: m.m	