

(RoHS Compliant) H3 N 25 A X - 2 XX SQ BK X 000 X
 1 1 2 3 4 5 6 7 8


- Insulator Material:
N = Nylon-6T
- P = Phosphor Bronze
Blank=Brass
- Per Row 02~50 pin
- Tail Style:
SQ = Straight
- Color: BK=Black
WH=White
- Contact Plated:
G=Gold Flash
A=Gold 3u"
D=Gold 5u"
G=Gold 10u"
L=Gold 15u"
U=Gold 30u"
- Special Options
A = PE Bag
B = Tube
D = Box

Current Rating: 1 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: -40° ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 Max Processing Temp: 260° C for 10 seconds
 Contact Material: Phosphor Bronze
 Insulator Material: Polyester, UL 94V-0
 Finish: Tin, Gold Plated
 Standard: Gold Flash all over
 Standard: Nylon-6T

Recommended P.C. Board
 Hole Layout

Part No.	Dim.A ±0.20	Dim.B ±0.20
H3N25AX-2XXS0BKX001X	2.60mm	3.00mm
H3N25AX-2XXS0BKX002X	2.60mm	1.80mm
H3N25AX-2XXS0BKX003X	1.50mm	3.00mm
H3N25AX-2XXS0BKX004X	1.50mm	1.80mm

①:H3N25A-2XXS0BKX000-2007/02/27-C

 CONN TOP COMPONENT INC.		PART NO H3N25AX-2XXS0BKX000X		.X ±0.3		.XXX ±0.100	
1:	H3N25A-2XXS0BKX00	DRAWING NO	PHB-00052	EDITION:	C1	ITEM: PHB	
BOM 2:	QT-0.46XXXXBN	DRAWN BY	GARY	2009/02/13	SCALE: 1:1		UNIT: m.m
3:	0	APPROVAL BY					

TEL:(02)86481727 FAX:(02)86482427