



Recommended P.C. Board
Hole Layout

Current Rating: 1 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: -40° ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 Max Processing Temp: 260° C for 10 seconds
 Contact Material: Phosphor Bronze
 Insulator Material: Polyester, UL 94V-0
 Standard: Nylon-6T
 Finish: Tin, Gold Plated
 Standard: Gold Flash all over

(RoHS Compliant) H4 N 25 A X - 2 XX R0 BK X 000 X
 1 1 2 3 4 5 6 7 8

- Insulator Material:
N = Nylon-6T
- P = Phosphor Bronze
Blank=Brass
- Per Row 02~50 pin
- Tail Style:
R0 = Right Angle
- Color: BK=Black
WH=White
- Contact Plated:
C=Gold Flash
A=Gold 3u"
D=Gold 5u"
G=Gold 10u"
L=Gold 15u"
U=Gold 30u"
- Special Options
A = PE Bog
D = Box
- Peckings:
A = PE Bog
D = Box

CONN TOP COMPONENT INC. ①:H4N25A-2XXR0BKX000-2007/02/27-C		PART NO		H4N25AX-2XXR0BKX000X		.X		.XX		.XXX	
1: H4N25A-2XXR0BKX000		DRAWING NO		PHC-00007		EDITION: C1		ITEM: PHC			
2: QT-0.46X10.20BN		DRAWN BY		GARY		2009/02/13		SCALE: 1:1			
3: QT-0.46X15.20BN		APPROVAL BY						UNIT: m.m			
TEL:(02)86481727 FAX:(02)86482427											