



Recommended P.C. Board
Hole Layout

Current Rating: 1 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: -40° ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 Max Processing Temp: 260° C for 10 seconds
 Contact Material: Phosphor Bronze
 Insulator Material: Polyester, UL 94V-0
 Standard: Nylon-6T
 Finish: Tin, Gold Plated
 Standard: Gold Flash all over

(RoHS Compliant) H4 N 25 A X - 2 XX S0 BK X 000 X
 1 2 3 4 5 6 7 8

- Insulator Material:
N= Nylon-6T
- P= Phosphor Bronze
Blank=Brass
- Per Row 02-50 pin
- Toill Style:
S0= Straight
- Color: BK=Black
WH=White
- Contact Plated:
C=Gold Flash
A=Gold 3u"
D=Gold 5u"
G=Gold 10u"
L=Gold 15u"
U=Gold 30u"
- Special Options
A = PE Bag
D = Box

①:H4N25A-2XXS0BKX000-2007/03/21-C		CONN TOP COMPONENT INC.		PART NO	H4N25AX-2XXS0BKX000X	.X	.XX	.XXX
1:	H4N25A-2XXBKH0	DRAWING NO		PHC-00002	EDITION: C1	±0.3	±0.20	±0.100
2:	QT-0.46X7.90BN	DRAWN BY		GARY	2009/02/13	ITEM: PHC		SCALE: 1:1
3:	0	APPROVAL BY				UNIT: m.m		
TEL:(02)86481727 FAX:(02)86482427								