



Recommended P.C. Board
Hole Layout

Current Rating: 1 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: - 40° ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 Max Processing Temp: 260° C for 10 seconds
 Contact Material: Phosphor Bronze
 Insulator Material: Polyester, UL 94V-0
 Standard: Nylon-6T
 Finish: Tin, Gold Plated
 Standard: Gold Flash all over

(RoHS Compliant) H4 N 25 AQ X - 2 XX S0 BK X 001 X
 1 2 3 4 5 6 7 8

- Insulator Material:
N = Nylon-6T
- P = Phosphor Bronze
Blank = Brass
- Per Row 02~50 pin
- Tail Style:
S0 = Straight
- Contact Plated:
C = Gold Flash
A = Gold 3u"
D = Gold 5u"
G = Gold 10u"
L = Gold 15u"
U = Gold 30u"
- Special Options
A = PE Bog
D = Box

CONN TOP
COMPONENT INC.

PART NO	H4N25AQX-2XXS0BKX001X	.X	.XX	.XXX
DRAWING NO	PHC-00022	EDITION:	C	ITEM: PHC
DRAWN BY	GARY	2008/03/26	SCALE: 1:1	UNIT: m.m
APPROVAL BY				

1: H4N25A-2XXBKX001
 2: QTP-0.46X0.535X9.60BN
 3:
 TEL: (02)86481727 FAX: (02)86482427