



Part No.	Dim.A ±0.20
P1X11XP-2XXS0BKXXM01X	3.20mm
P1X11XP-2XXS0BKXXM02X	6.00mm
P1X11XP-2XXS0BKXXM03X	7.90mm
P1X11XP-2XXS0BKXXM04X	12.00mm
P1X11XP-2XXS0BKXXM05X	2.30mm
P1X11XP-2XXS0BKXXM06X	12.30mm

- Standard: A=P.B.T.
N=Nylon-6T
- Contact Material:
A=Phosphor Bronze
B=Brass
3. P=With Ke
4. Per ROW 02 to 40
5. Tail Style: S0= Straight
6. Color: BK=Black
- Contact Plated:
T=Matte Tin over Nickel
W=Matte Tin over Nickel 150u"
Y=Bright Tin over Nickel
C=Gold Flash
F=Gold Flash, Tin 100u"
A=Gold 3u"
B=Gold 3u", Tin 100u"
- M=Gold 5u"
E=Gold 5u", Tin 100u"
G=Gold 10u"
J=Gold 10u", Tin 100u"
L=Gold 15u"
M=Gold 15u", Tin 100u"
U=Gold 30u"
V=Gold 30u", Tin 100u"
- Packaging:
B=Tube
C=Tray
D=Box

(RoHS Compliant)

P1 X 11 X P - 2 XX S0 BK X M00 X

1 2 3 4 5 6 7 8 8

©P1X11XP-2XXS0BKXXM00-2007/03/21-C

CONN TOP COMPONENT INC.

1: P1X11P-2XXBKHH0	DRAWING NO	PB-00037	EDITION: C1	ITEM: PB
2: P1X11T-6066XXSX	DRAWN BY	LN	2009/01/12	SCALE: 1:1
3:	APPROVAL BY			UNIT: m.m

TEL:(02)86481727 FAX:(02)86482427

Current Rating: 3 Amps

Insulator Resistance: 5000 Megohms min

Contact Resistance: 20 m ohms max

Dielectric Withstanding: 1000 V AC

Operating Temperature: -40° ~ +105° C

Contact Material: Phosphor Bronze Brass

Insulator Material: Polyester, UL 94V-0 Standard: PBT

Finish: Tin, Gold Plated

Standard: Gold Flash all over

Note: Duplex Plating: Gold Plated on contact area, Tin on solder area

Insulator Material: Polyester, UL 94V-0 Standard: Nylon-6T

Max Processing Temp: 230° C for 60 seconds 260° C for 10 seconds

Recommended P.C. Board Hole Layout