



Current Rating: 1 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: -40° ~ +125° C
 Max Processing Temp: 230° C for 60 seconds
 Contact Material: 260° C for 10 seconds
 Insulator Material: Phosphor Bronze
 Polyester, UL 94V-0
 Standard: L,C,P
 Finish: Tin, Gold Plated
 Standard: Gold Flash all over nickel

Recommended P.C. Board
 SMD Layout

(RoHS Compliant)
 (Halogen-Free)

P3 L 35 - 2 XX S0 BK X 000 B
 1 2 3 4 5 6 7

- Standard: L=LCP
- Per ROW 02 to 50
- Taill Style: S0 = Straight
- Color: BK=Black
- Contact Plated: C=Gold Flash
- Special Options: D=Gold 5u", G=Gold 10u", L=Gold 15u", U=Gold 30u"
- Packing: B = Tube



CONN TOP COMPONENT INC.		PART NO	P3L35-2XXS0BKX000B	X	±0.3	.XXX	±0.100
1:	P3L35-2XXBKHH0	DRAWING NO	P127-00178	EDITION:	C	ITEM:	P127
2:	P3X35T-1520-01S	DRAWN BY	GARY	2009/03/09	SCALE:	1:1	
3:	P3X35T-1520-02S	APPROVAL BY				UNIT:	m.m
TEL: (02)86481727 FAX: (02)86482427							