



Current Rating: 1 Amps  
 Insulator Resistance: 5000 Megohms min  
 Contact Resistance: 20 m ohms max  
 Dielectric Withstanding: 500 V AC  
 Operating Temperature: -40° ~ +125° C  
 Max Processing Temp: 230° C for 60 seconds  
 260° C for 10 seconds  
 Contact Material: Phosphor Bronze  
 Insulator Material: Polyester, UL 94V-0  
 Standard: LCP  
 Finish: Tin, Gold Plated  
 Standard: Gold Flash all over

Recommended P.C. Board  
 SMD Layout

(RoHS Compliant)  
 (Halogen-Free)

P3 L 43 - 2 XX D1 BK X 000 B

1 1 2 3 4 5 6 7

- Standard: L=LCP
- Per ROW 02 to 50
- Toll Style: D1=With Peg
- Color: BK=Black
- Contact Plated: C=Gold Flash
- Contact Options: D=Gold 5u", G=Gold 10u", L=Gold 15u", U=Gold 30u"
- Packing: B= Tube
- Special Options: A=Gold 3u"



CONN TOP COMPONENT INC.  
 @:2:45-2008/12/01-C  
 @:P3L43T-1534-01D-2008/12/01-C

1: P3L43-2XXBKHI  
 2: @:P3L43T-1534-03D  
 3: BOM

PART NO	P3L43-2XXD1BKX000B	.X	.XX	.XXX
DRAWING NO	P127-00159	±0.3	±0.20	±0.100
DRAWN BY	GARY	EDITION: C1	ITEM: P127	SCALE: 1:1
APPROVAL BY		2009/05/27	UNIT: m.m	

TEL:(02)86481727 FAX:(02)86482427