



Current Rating: 1 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: -40° ~ +125° C
 Max Processing Temp: 230° C for 60 seconds
 260° C for 10 seconds
 Contact Material: Phosphor Bronze
 Insulator Material: Polyester, UL 94V-0
 Standard: LCP
 Finish: Tin, Gold Plated
 Standard: Gold Flash all over

Recommended P.C. Board
 SMD Layout

(RoHS Compliant)
 (Halogen-Free)

P3 L 43 - 2 XX D2 BK X 000 B
 1 2 3 4 5 6 7

- Standard: L=LCP
- Per ROW 02 to 50
- Tail Style: D2=With Peg
 $\phi 1.20 \times 0.80$ Type
- Color: BK=Black
- Contact Plated: C=Gold Flash
 A=Gold 3u"
- Special Options: D=Gold 5u"
 G=Gold 10u"
 L=Gold 15u"
 U=Gold 30u"
 B= Tube
- Packing: B= Tube



PART NO	P3L43-2XXD2BKX000B	.X	.XX	.XXX
DRAWING NO	P127-00189	±0.3	±0.20	±0.100
DRAWN BY	GARY		ITEM: P127	SCALE: 1:1
APPROVAL BY			UNIT: m.m	

1: P3L43-2XXBKHX2
 BOM 2: P3L43T-1534-03D
 3: APPROVAL BY

CONN TOP COMPONENT INC.
 TEL: (02)86481727 FAX: (02)86482427