



Current Rating: 1 Amps  
 Insulator Resistance: 5000 Megohms min  
 Contact Resistance: 20 m ohms max  
 Dielectric Withstanding: 500 V AC  
 Operating Temperature: -40° ~ +125° C  
 Max Processing Temp: 230° C for 60 seconds  
 260° C for 10 seconds  
 Contact Material: Phosphor Bronze  
 Insulator Material: Polyester, UL 94V-0  
 Standard: LCP

Finish: Tin, Gold Plated  
 Standard: Gold Flash all over

Recommended P.C. Board  
 SMD Layout

(RoHS Compliant)  
 (Halogen-Free)

P3 L 43 P - 2 XX D2 BK X 000 B

1 2 3 4 5 6 7 8

- Standard: L=LCP
- Per ROW 02 to 50
- Toill Style: D2=With Peg  
ø1.20x0.80 Type
- Color: BK=Black
- Contact Plated: C=Gold Flash  
A=Gold 3u"
- Special Options: D=Gold 5u"  
G=Gold 10u"  
L=Gold 15u"  
U=Gold 30u"  
B= Tube
- Packings: B= Tube

CONN TOP COMPONENT INC.  
 P3L43P-2XXXBKH2  
 P127-00161  
 GARY  
 2009/05/27

PART NO	P3L43P-2XXXD2BKX000B	.X	.XXX
DRAWING NO	P127-00161	±0.3	±0.100
DRAWN BY	GARY	EDITION: C1	ITEM: P127
APPROVAL BY		SCALE: 1:1	UNIT: m.m

TEL: (02)86481727 FAX: (02)86482427