



Recommended P.C. Board
Hole Layout

Current Rating: 1 Amps
 Insulator Resistance: 1000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: -40° ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 260° C for 10 seconds
 Contact Material: Phosphor Bronze
 Insulator Material: Polyester, UL 94V-0
 Standard: LCP
 Finish: Tin, Gold Plated
 Standard: Gold Flash all over

(RoHS Compliant)
(Halogen-Free)

P3 L 45 - 1 XX S0 BK X 001 B
 1 2 3 4 5 6 7

- Standard: L=LCP
- Per ROW 02 to 50
- Taill Style: SO= Straight
- Color: BK=Black
- Contact Plated: C=Gold Flash
- Special Options: D=Gold 5u", G=Gold 10u", L=Gold 15u", U=Gold 30u"
- Packing: B= Tube



CONN TOP
COMPONENT INC.
 @:P3L43T-1534-02S-2008/12/09-C
 @:2:65-2008/12/09-C

1:	P3L45-1XXBKHO
2:	@:P3L43T-1534-04S
3:	

BOM
 TEL:(02)86481727 FAX:(02)86482427

PART NO	P3L45-1XXS0BKX001B	.X	.XX	.XXX
DRAWING NO	P127-00162	±0.3	±0.20	±0.100
DRAWN BY	GARY	EDITION: C1	ITEM: P127	SCALE: 1:1
APPROVAL BY		2009/05/25		UNIT: m.m