



Current Rating: 1 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20m ohms max.
 Dielectric Withstanding: 500 V AC
 Operating Temperature: -40° ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 Max Processing Temp: 260° C for 10 seconds
 Contact Material: Copper Alloy
 Insulator Material: Polyester, UL 94V-0
 Standard: Nylon-6T
 Finish: Tin, Gold Plated
 Standard: Gold Flash all over

Recommended P.C. Board
SMD Layout

(RoHS Compliant) P3 N 23 - 2 XX D2 BK X 000 B

- Standard: N= Nylon-6T
- Per ROW 02 to 50
- Tail Style: D2 = S.M.D With Peg Type
- Color: BK=Black
- Contact Plated: C=Gold Flash
- Contact Style: A=Gold 3u"
- Special Options: D=Gold 5u", G=Gold 10u", L=Gold 15u", U=Gold 30u"
- Packing: B= Tube

©:P3N23-2XXD2BKX000-2008/01/23-C1 ©:P127T-1218-01D-15-402-10pin-2007/04/18-C			
I: P3N23-2XXBKH2 BOM 2: ©: P127T-1218-01D 3:		PART NO P3N23-2XXD2BKX000B DRAWING NO P127-00031 DRAWN BY GARY APPROVAL BY	
		.X ±0.3	.XX ±0.20
		EDITION: C2	
		SCALE: 1:1	
		ITEM: P127	
		UNIT: m.m	